



ELECTRONIC DEVICE WITH PAGING FOR ENERGY CURTAILMENT AND CODE GENERATION FOR MANUAL VERIFICATION OF CURTAILMENT

ELECTRONIC DEVICE WITH PAGING FOR ENERGY CURTAILMENT AND CODE GENERATION FOR MANUAL VERIFICATION OF CURTAILMENT

Technical Field

5 This invention relates generally to electronic devices, and is more particularly directed toward systems and methods for requesting energy curtailment through the use of communications with an electronic device.

Background

10 Blackouts are sometimes caused because of a failure of the utility company's power system. Sometimes a failure is caused by a malfunction in the system. In addition, certain events (e.g., a hurricane, tornado, lightning storm, etc.) can damage parts of the system that in turn result in a blackout or partial blackout. However, sometimes blackouts can be caused by a demand for power resources that exceeds the supply of power available. In times of peak usage, energy providers may
15 be susceptible to blackouts or brownouts because of power shortages. Blackouts or brownouts may be avoided by instructing users of the system to reduce their power consumption during power shortages. In addition, power may be conserved by requesting that users of the system reduce their power consumption. It would be beneficial to use modern computer and communications technology to reduce the likelihood of power outages or shortages.

20 Computer and communication technologies continue to advance at a rapid pace. Indeed, computer and communication technologies are involved in many aspects of a person's day. For example, many devices being used today by consumers have a small computer inside of the device. These small computers come in varying sizes and degrees of sophistication. These small computers include everything from one microcontroller to a fully-functional complete computer system. For
25 example, these small computers may be a one-chip computer, such as a microcontroller, a one-board type of computer, such as a controller, a typical desktop computer, such as an IBM-PC compatible, etc.

 Computers typically have one or more processors at the heart of the computer. The processor(s) usually are interconnected to different external inputs and outputs and function to

manage the particular computer or device. For example, a processor in a thermostat may be connected to buttons used to select the temperature setting, to the furnace or air conditioner to change the temperature, and to temperature sensors to read and display the current temperature on a display.

5 Many appliances, devices, etc., include one or more small computers. For example, thermostats, furnaces, air conditioning systems, refrigerators, telephones, typewriters, automobiles, vending machines, and many different types of industrial equipment now typically have small computers, or processors, inside of them. Computer software runs the processors of these computers and tells the processors what to do to carry out certain tasks. For example, the computer
10 software running on a thermostat may cause an air conditioner to stop running when a particular temperature is reached or may cause a heater to turn on when needed.

These types of small computers that are a part of a device, appliance, tool, etc., are often referred to as embedded systems. The term "embedded system" usually refers to computer hardware and software that is part of a larger system. Embedded systems may not have typical
15 input and output devices such as a keyboard, mouse, and/or monitor. Usually, at the heart of each embedded system is one or more processor(s).

Embedded systems may be used to control or monitor the use of certain resources. For example, an embedded system may be used to control and/or monitor the power used, the water used, the temperature, the lighting, etc. Benefits may be realized through the use of embedded
20 systems to control and/or monitor the use of resources.

Summary of the Invention

A curtailment module is disclosed for enabling an energy provider to send a request to curtail energy use to a user. The curtailment module includes an interface for electronic
25 communications with a temperature control device. A paging module is used to receive the request from the energy provider through a paging network. The curtailment module also includes a processor in electronic communication with the paging module for receiving the request from the paging module. Memory is also included and is in electronic communication with the processor.

The memory of the curtailment module may be programmed for particular tasks. For example, the memory may be programmed with instructions to cause the curtailment module to receive the request from the energy provider. In addition, the memory may be programmed with instructions for communicating with the temperature control device. Further, the memory may be programmed to cause the processor to store history data relating to the temperature control device. The memory may also be programmed with instructions to generate a verification code to verify whether the request was followed. The verification code instructions may use a device ID, the history data and/or a curtailment message in generating the verification code.

Embodiments of the curtailment module may also include a display for outputting information to the user and an input device for enabling the user to enter a user input. The verification code may be displayed to the user using the display.

The temperature control device may be used to control the temperature of a structure remotely located from the energy provider. The structure broadly includes any structure at a location that uses a heating unit and/or a cooling unit to affect the temperature of the structure.

A method is also disclosed for requesting that energy use be curtailed at the structure and for verifying curtailment. The method includes creating a curtailment message to send to the structure, sending the curtailment message to the structure through a pager network, receiving the curtailment message by a curtailment module at the structure, displaying the curtailment message at the structure, monitoring the temperature control device in electronic communication with the curtailment module, saving history data that relates to settings from the temperature control device, generating a verification code that verifies whether the curtailment message was followed, and displaying the verification code at the structure for the user.

Brief Description of the Drawings

The present embodiments will become more fully apparent from the following description and appended claims, taken in conjunction with the accompanying drawings. Understanding that these drawings depict only typical embodiments and are, therefore, not to be considered limiting of the invention's scope, the embodiments will be described with additional specificity and detail through use of the accompanying drawings in which:

Figure 1 is a block diagram of an embodiment illustrating the use of a paging network to request energy curtailment;

Figure 2 is a block diagram of another embodiment illustrating the use of a paging network to request energy curtailment;

5 Figure 3 is a block diagram of an embodiment illustrating the use of a message center and paging network to request energy curtailment;

Figure 4 is a block diagram of an embodiment of an energy provider;

Figure 5 is a block diagram of an embodiment of a curtailment message;

Figure 6 is a block diagram of another embodiment of a curtailment message;

10 Figure 7 is a block diagram illustrating hardware components of an embodiment of a message center;

Figure 8 is a block diagram illustrating software components of an embodiment of a message center;

15 Figure 9 is a block diagram illustrating hardware components of an embodiment of a curtailment module;

Figure 10 is a block diagram illustrating software components of an embodiment of a curtailment module; and

Figure 11 is a flow diagram of a method for requesting energy curtailment and for verification of the curtailment.

20

Detailed Description

It will be readily understood that the components of the embodiments as generally described and illustrated in the Figures herein, could be arranged and designed in a wide variety of different configurations. Thus, the following more detailed description of the embodiments of the system and method of the present invention, as represented in the Figures, is not intended to limit the scope
25 of the invention, as claimed, but is merely representative of the embodiments of the invention.

Figure 1 is a block diagram of an embodiment of a system 20 illustrating the use of a paging network 22 to request energy curtailment by a user at a particular structure 23 at a location. An energy provider 24 (e.g., a power company, a utility company, etc.) may desire to request that its

users curtail or decrease their power consumption at a particular time or times. For example, an energy provider 24 may desire to request that its users decrease their power consumption by a particular amount at peak use times. Energy providers 24 may request the curtailment through a specific request relating to the use of temperature control of the structure 23. As will be explained below, such a request may ask the user to reduce the use of an air conditioner or the use of a heater in order to save energy.

The structure 23 refers to any structure that uses energy to control the temperature of the structure. For example, a structure 23 may be a home, a garage, an office, a warehouse, a studio, an arena, a store, etc.

To request curtailment, the energy provider 24 may send a page to a curtailment module 26 at the structure 23 to request a curtailment. As shown in Figure 1, the curtailment module 26 may be a separate component in relation to the temperature control device 28. Typically users will already have a temperature control device 28 (e.g., a thermostat) at their location. The curtailment module 26 receives the curtailment request from the paging network 22 and notifies the user of the request. The curtailment module 26 also is in communication with the temperature control device 28 to verify curtailment.

The temperature control device 28 may be in electronic communication with a heating unit 27 and/or a cooling unit 29. The heating unit 27 and the cooling unit 29 operate to affect the temperature of the structure 23.

Figure 2 is a block diagram of another embodiment of a system 30 illustrating the use of a paging network 22 to request energy curtailment. Figure 2 illustrates a combined temperature control device and curtailment module 32. Those skilled in the art will appreciate that the hardware and/or software components of the curtailment module 26 may be combined with a temperature control device 28 for a combination temperature control device and curtailment module 32. The combination temperature control device and curtailment module 32 is in electronic communication with the heating unit 27 and/or the cooling unit 29.

Figure 3 is a block diagram of an embodiment of a system 34 illustrating the use of a message center 36 and paging network 22 to request energy curtailment. The message center 36 may be provided to handle the sending of messages through the paging network 22 to the

curtailment modules 26 at various structures 23. The message center 36 will be more fully discussed below.

Figure 4 is a block diagram of an embodiment of an energy provider 24. Many energy providers 24 are in existence and use commercially available billing systems 38 for billing users for the use of power or energy. Thus, those skilled in the art will appreciate the various types of billing systems 38 that may be used by an energy provider 24.

The energy provider 24 includes curtailment messages 40. The curtailment messages 40 allow an embodiment of an energy provider 24 to verify curtailment for users and give any due credit to the user. The curtailment verification 42 functionality verifies whether the user actually curtailed his or her power or energy use. As will be disclosed below, a code may be generated that can be used to verify curtailment. The curtailment verification 42 functionality may perform similar steps as will be described herein to verify curtailment.

Figure 5 is a block diagram of an embodiment of a curtailment message 40. A curtailment message 40 may include several curtailment requests 44. For example, Figure 5 illustrates three curtailment requests 44a, 44b, 44c in the curtailment message 40. Each curtailment request 44 of the embodiment shown in Figure 5 illustrates data fields included in the request 44. The data includes fields for the date 46 of the requested curtailment, for the time(s) 48 of the curtailment, the curtailment 50, and the savings 52 to the user should the user curtail as requested. Other 54 data fields may also be included in the curtailment request 44 as needed. The curtailment field 50 indicates what curtailment is being requested. For example, the curtailment field 50 may indicate to the user to reduce his or her power or energy consumption by a certain percent. Alternatively, the curtailment field 50 may indicate to the user to change the setting on his or her thermostat by a specific amount. Those skilled in the art will appreciate the various types of curtailment requests that could be made. The savings field 52 indicates to the user what the savings or credits will be if the curtailment is followed. For example, the savings may be a reduction of the cost to the user by a certain percent. Alternatively, it may be a rebate of a certain amount. Those skilled in the art will appreciate that various other types of savings and/or credits may be given to users for curtailing as requested.

Figure 6 is a block diagram of another embodiment of a curtailment message 56. The curtailment message 56 may include several curtailment requests 58. Figure 6 illustrates three curtailment requests 58a, 58b, 58c in the curtailment message 56. Each curtailment request 58 of the embodiment shown in Figure 6 also illustrates data fields included in the request 58. The data includes fields for the time(s) 60 of the curtailment, the curtailment type 62, and the curtailment value 64.

The time field 60 may be used to indicate at what time a curtailment should begin. Those skilled in the art will appreciate that the time field 60 may be formatted to include a number of beginning times and a number of ending times. If no date were included in the time field 60, the embodiment sending this message may be configured to send out curtailment messages on the day of the curtailment, or a specified number of days before the curtailment, such that the curtailment module 26 may obtain the date to be associated with the particular times. Alternatively, no date included may be used to indicate that the curtailment message 56 is effective for each day until a new curtailment message 56 is broadcast.

The curtailment type field 62 indicates what type of curtailment is being requested. For example, the curtailment type field 62 may indicate to the user to reduce his or her power or energy consumption by a certain percent. Alternatively, the curtailment type field 62 may indicate to the user to change the setting on his or her thermostat by a specific amount. Further, a variable curtailment type 62 may be requested indicating to the user that, depending on how much curtailing is accomplished, the user will realize proportionate savings. The curtailment value field 64 is associated with the curtailment type 62 to define the curtailment request. For example, if the curtailment type 62 indicated that the curtailment request was requesting a certain percentage reduction in power consumption associated with air conditioning a structure 23, the curtailment value 64 may be a number defining the exact percentage. By way of further example, if the curtailment type 62 indicated to a user to reduce the temperature setting on his or her thermostat by a fixed number of degrees, the curtailment value 64 may be used to define the fixed number (e.g., a curtailment value of 3 to define the fixed number of degrees to 3 degrees).

Figure 7 is a block diagram of hardware components that may be used in an embodiment of a message center 66. As illustrated in Figure 3, a message center 66 may be used to handle the

sending of messages through the paging network 22 to the curtailment modules 26 at various locations. The communications link between the energy provider 24 and the message center 36, 66 may be based on standard protocols and security.

The embodiment of a message center 66 shown in Figure 7 communicates with the curtailment module(s) 26 through the paging network 22. One possible paging network 22 that may be used is the paging network provided by SkyTel Communications, Inc. Paging units/modules 68 that can communicate using paging networks 22 are commercially available.

The message center 66 may route messages to the network operations center (not shown) for the paging network 22. The use of paging networks and sending/receiving pages is known in the art.

The paging module 68 used to communicate with the curtailment module 26 may be configured for single direction paging (one-way paging) from the energy provider 24 and/or message center 66 to the curtailment module 26. Using one-way paging typically reduces the cost of the paging service and the components required to send and receive pages. Of course, it will be appreciated that two-way paging may be used.

A computer may be used to implement the message center 66. Many different types of computer systems may be used to implement the message center 66. The diagram of Figure 7 illustrates typical components of a computer system including a processor 67, memory 69, a storage device 71, an input device 73, and an output device 75. One or more communication ports 77 may also be included in the message center 66. It will be appreciated by those skilled in the art that many more components may be included in the message center 66. For example, several input devices 73 may be included, such as a keyboard, a mouse, a joystick, a touchscreen, etc. In addition, several output devices may be included such as a monitor, speakers, a printer, etc. Thus, those skilled in the art will appreciate that many additional components may be added to the message center 66 without detracting from the functionality to serve as a message center 66.

Figure 8 illustrates components of an embodiment of a message center 66 that may be implemented through software and/or stored data on the storage 71 or memory 69 of the message center 66. A message handler 72 may handle messages being communicated through the paging

module 68 and paging network 22. The message handler 72 may read and write data to and from the paging module 68 in order to send and receive messages through the paging network 22.

The message center 66 may include a message queue 70 to queue up the curtailment messages 76 to be sent out, or to queue up messages being received.

5 Customer identifications 74 may be included at the message center 66 to identify the various customers that may receive curtailment messages 76. Customer identification data 74 may include as much information as the message center 66 and/or the energy provider 24 deem necessary or appropriate. For example, a customer identification may include the name of the customer (not shown), the address (not shown), the telephone number (not shown), the device
10 identification, etc.

The curtailment messages 76 may also be stored at the message center 66. The curtailment messages 76 may include all the curtailment messages sent out, or it may only keep a certain number of messages that have been sent out.

15 Figure 9 is a block diagram illustrating hardware components of an embodiment of a curtailment module 26. An embodiment of a curtailment module 26 includes a processor 78 and memory 80. Those skilled in the art will appreciate the various types of processors and memory that can be used. For example, an embodiment of the curtailment module 26 may include a single-board computer that includes the processor 78 and memory 80. Such single-board computers are commercially available. Alternatively, the curtailment module 26 may include a
20 microcontroller as the processor 78. In addition, embodiments of the curtailment module 26 may include flash memory.

The curtailment module 26 may also include communications ports 82. The communications ports 82 enable communication with other electronic devices. Those skilled in the art will appreciate the various types of communication ports that can be used with the
25 embodiments herein.

A paging module 84 is included in the curtailment module 26 for communications through the paging network 22. Paging units or modules 84 that are capable of receiving pages through a paging network 22 are commercially available. One such commercially available pager communications module is the CreaLink receiver module available from Motorola, Inc.

The embodiment of Figure 9 also includes a keypad 86 or a set of buttons or switches for input. Through the input means a user may navigate through menus, cause curtailment messages to be displayed, cause the verification code to be displayed, etc. The keypad 86, or any other input means that could be used with the curtailment module 26, is used to by the user to enter user inputs. Other input means may include a touch screen, switches, sensors, a keyboard, a mouse, a joystick, etc. It will be appreciated by one skilled in the art that many different types of input means may be used with the curtailment module 26.

An embodiment of a curtailment module 26 may also include a display 88 or other output device to present information to the user. For example, when a curtailment message 40, 56 is sent to the curtailment module 26, the message or information relating to the message may be displayed to the user on a display 88. A typical display used is an LCD. Other output devices may also be used. For example, a speaker for voice messages to the user could be used, a printer may also be used to print information for the user. In addition, the curtailment module 26 may not directly present information to the user but may send information to another device for presenting the information to the user. For example, the curtailment module 26 may send information to a telephone (not shown), a television (not shown), a personal computer (not shown), etc., for that particular device to present the information to the user.

The embodiments disclosed herein may be used to send curtailment messages 40, 56 that relate to temperature control. Those skilled in the art will appreciate, however, that curtailment messages 40, 56 could be sent regarding other resources such as overall power used, water used, telephone usage, etc. Depending upon the type of resource being curtailed, the curtailment module 26 may be in electronic communication with various kinds of devices. For temperature control, the curtailment module 26 may include an interface 90 for the temperature control device 28. This interface 90 is used to establish electronic communications with the temperature control device 28, which may be a thermostat (not shown).

For the embodiment used for temperature control by interfacing with a thermostat, the particular design of the interface 90 will depend upon the capabilities and/or functionality of the thermostat. The curtailment module 26 monitors the settings and/or readings of the thermostat in order to be able to verify that any curtailments were or were not followed. For a particular

thermostat's specifications, those skilled in the art would appreciate how to communicate with the thermostat.

Alternatively, and as shown in Figure 2, the curtailment module 26 and the temperature control device 28 may be combined to form a combination temperature control device with curtailment module 32. If a combination module 32 were used, an interface 90 for the temperature controller may not be needed because of the integration of the two components.

Figure 10 is a block diagram illustrating software components of an embodiment of a curtailment module 26. Although the items of Figure 10 are described as being software components, it will be appreciated that hardware components may be substituted for various software components. In addition, some hardware components may be achieved through software components.

A customer identification 92 may be stored to identify the customer. A device identification 94 may be stored to identify the curtailment module 26 being used. In addition, the curtailment messages 98 may be stored by the curtailment module 26. Depending upon the number of messages 98 being received, and depending upon the amount of memory 80 available, either all of the messages 98 may be stored or only a certain number of messages 98 may be stored.

The past settings of the temperature control device 28, as well as the past readings of the temperature control device 28, may be stored in history data 100. For example, the temperature reading at periodic intervals may be stored for later use. In addition, the user's settings of the desired temperature may also be stored. Through use of the curtailment messages 98 and of the history data 100, a verification code 102 or codes 102 may be generated.

Energy provider's 24 may offer savings or credits to users if they curtail as requested. For user's to get the savings or credits, they may be instructed to contact their energy provider 24 through some means and report to their provider 24 the verification code(s) 102. The user may make a telephone call to the provider 24 to request the savings, or the user may send an e-mail to a particular address requesting the savings, or the user may complete an online form to receive the savings, etc. The verification code(s) 102 are used by the energy provider 24 to verify whether the user actually did curtail as instructed or requested.

The code generator 104 generates the verification code(s) 102 based on the user's inputs to

the curtailment module 26 and to the temperature control device 28. For example, if a curtailment message 98 indicated to the user to reduce the temperature setting on the user's thermostat by two percent between 2 p.m and 5 p.m., the code generator 104, using the history data 100, would generate a code 102 that would indicate to the energy provider 24 whether the user actually reduced the temperature setting by two percent for the three hours requested.

The code generator 104 is a function that takes inputs and generates output. In one embodiment, the code generate 104 may be a hash function. The hash function takes as inputs the curtailment message 98, or parts of the message 98, and the history data 100, or parts of the history data 100, to generate the verification code 102. Of course, other pieces of data may also be used as input parameters to the hash function to generate a verification code 102.

Several different hash functions may be stored by the curtailment module 26. If more than one code generator 104 is available, the verification code 102 may be generated by a particular code generator 104 indicated by a data field in the curtailment message 98.

The code generator 104 may be implemented through various types of functions that produce output. For example, the code generator 104 may include a CRC function (not shown). In addition, the code generator 104 may include a cryptographic function, such as DES.

Figure 11 is a flow diagram of a method for requesting energy curtailment and for verification of the curtailment. An energy provider 24 may send 106 a message to the curtailment module 26 to curtail energy use in some way. The curtailment module 26 receives 108 the message. The curtailment message 40, 56 may be stored 110 and/or displayed 110. The curtailment module 26 monitors 112 the temperature control device 28 for actual curtailment and generates 114 a code 102 for curtailment verification.

Once the code 102 has been generated, the verification code 102 may be stored 116 and/or displayed 116 for use by the user in curtailment verification. To verify curtailment, the user presents 118 the curtailment verification code 102 to the energy provider 24 for any curtailment savings or credit.

The present invention may be embodied in other specific forms without departing from its spirit or essential characteristics. The described embodiments are to be considered in all respects only as illustrative, and not restrictive. The scope of the invention is, therefore, indicated by the

appended claims, rather than by the foregoing description. All changes which come within the meaning and range of equivalency of the claims are to be embraced within their scope.

What is claimed is:

1970	1971	1972	1973	1974	1975	1976	1977	1978	1979	1980	1981	1982	1983	1984	1985	1986	1987	1988	1989	1990	1991	1992	1993	1994	1995	1996	1997	1998	1999	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2027	2028	2029	2030	2031	2032	2033	2034	2035	2036	2037	2038	2039	2040	2041	2042	2043	2044	2045	2046	2047	2048	2049	2050	2051	2052	2053	2054	2055	2056	2057	2058	2059	2060	2061	2062	2063	2064	2065	2066	2067	2068	2069	2070	2071	2072	2073	2074	2075	2076	2077	2078	2079	2080	2081	2082	2083	2084	2085	2086	2087	2088	2089	2090	2091	2092	2093	2094	2095	2096	2097	2098	2099	2100	2101	2102	2103	2104	2105	2106	2107	2108	2109	2110	2111	2112	2113	2114	2115	2116	2117	2118	2119	2120	2121	2122	2123	2124	2125	2126	2127	2128	2129	2130	2131	2132	2133	2134	2135	2136	2137	2138	2139	2140	2141	2142	2143	2144	2145	2146	2147	2148	2149	2150	2151	2152	2153	2154	2155	2156	2157	2158	2159	2160	2161	2162	2163	2164	2165	2166	2167	2168	2169	2170	2171	2172	2173	2174	2175	2176	2177	2178	2179	2180	2181	2182	2183	2184	2185	2186	2187	2188	2189	2190	2191	2192	2193	2194	2195	2196	2197	2198	2199	2200	2201	2202	2203	2204	2205	2206	2207	2208	2209	2210	2211	2212	2213	2214	2215	2216	2217	2218	2219	2220	2221	2222	2223	2224	2225	2226	2227	2228	2229	2230	2231	2232	2233	2234	2235	2236	2237	2238	2239	2240	2241	2242	2243	2244	2245	2246	2247	2248	2249	2250	2251	2252	2253	2254	2255	2256	2257	2258	2259	2260	2261	2262	2263	2264	2265	2266	2267	2268	2269	2270	2271	2272	2273	2274	2275	2276	2277	2278	2279	2280	2281	2282	2283	2284	2285	2286	2287	2288	2289	2290	2291	2292	2293	2294	2295	2296	2297	2298	2299	2300	2301	2302	2303	2304	2305	2306	2307	2308	2309	2310	2311	2312	2313	2314	2315	2316	2317	2318	2319	2320	2321	2322	2323	2324	2325	2326	2327	2328	2329	2330	2331	2332	2333	2334	2335	2336	2337	2338	2339	2340	2341	2342	2343	2344	2345	2346	2347	2348	2349	2350	2351	2352	2353	2354	2355	2356	2357	2358	2359	2360	2361	2362	2363	2364	2365	2366	2367	2368	2369	2370	2371	2372	2373	2374	2375	2376	2377	2378</
------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	--------